

FOR SALE BY PRIVATE TREATY

SURPLUS TO THE ONGOING OPERATIONS OF TIMKEN STEEL

FEATURING: 6-3/4" (172mm) Complete Seamless Pipe Line, Loeser Tube and Bar Grinding and Polishing Line, Reika Tube Recut w/Chamfering Line, (2) SES Ingot Mold Transfer Carts, Olson Industries Car Bottom Furnace

TIMKEN STEEL



PREVIEW & INSPECTION: By Appointment Only

PREVIEW LOCATION: Canton, OH



6-3/4" (172mm) Complete Seamless Pipe Line

COVID protocols will require health declaration, mask wearing and social distancing as condition of entry.

FOR FURTHER INFORMATION CONTACT: Nyk Westbrook at 818.738.0800 or email nwestbrook@maynards.com

SALE CONDUCTED BY:

Maynards
SINCE 1902

AUCTIONS | LIQUIDATIONS | APPRAISALS

21700 Northwestern Hwy., Suite 1180
Southfield, MI 48075

248.569.9781 | maynards.com

SALE IN CONJUNCTION WITH:

GALAXIE CORPORATION
Worldwide Metalworking Equipment Dealer

NATIONAL MACHINERY EXCHANGE, INC.

SEAMLESS PIPE LINE

- **6-3/4" (172mm) Complete Seamless Pipe Line:** OD Range: 1.90"-6.75" (48mm-172mm); ID Range: 1"-4.25" (25mm-108mm); Maximum Lengths: 34' (10m) (Cooling Bed Product); 32' (9.75m) (Mill Anneal Product); Billet Sizes: Diameter – 3.25"-7.5" (82.5mm-190.5mm), Lengths – 3'-6"-13' (1,066mm-3,962mm)
OPERATING VIDEO AVAILABLE AT: www.maynards.com



6-3/4" (172mm) Complete Seamless Pipe Line

TUBE AND BAR GRINDING AND POLISHING LINE

- **12" (300mm) Loeser Tube and Bar Grinding and Polishing Line (2015):** Product: Hot Rolled and Drawn Tubes; Diameter Range: 2.362"-12" (60mm-300mm); Length Range: 9.8'-44.3' (3m-13.5m); Weight Capacity: 6,600 lbs (3,000 kg)



12" (300mm) LOESER Tube and Bar Grinding and Polishing Line

TUBE RECUT WITH CHAMFERING LINE

- (2) 7.5" (190mm) Reika Tube Recut w/Chamfering Line

General Specifications Cut Off A: Tube Diameter Range: 3"-7.5" (76.2mm-190.5mm); Wall Thickness Range: 0.157"-0.70" (4mm-17.78mm); Incoming Tube Length: 12'-60' (2,438mm-13,716mm); Cut Off Head Speed: 200 RPM to 1,000 RPM

General Specifications Cut Off B: Tube Diameter Range: 1.181"-5.512" (30mm-140mm); Wall Thickness Range: 0.157"-1.2" (4mm-30mm); Incoming Tube Length: 10'-42' (3,000mm-13,000mm); Cut Off Head Speed: 200 RPM to 1,000 RPM



7.5" (190mm) REIKA Tube Recut w/Chamfering Line

SES INGOT MOLD TRANSFER CARTS

- (2) OD 270-Ton Capacity SES Ingot Mold Transfer Carts: Load Capacity: 24 Ingots; Weight Capacity: 270-Tons; Car Speed: 50 FPM



OD 270-Ton Capacity SES Ingot Mold Transfer Cart

CAR BOTTOM FURNACE

- 50' Olson Industries Car Bottom Furnace (2011): Heating: Natural Gas; 24 Burners; Operating Temperature Range: 600-2,300 Degrees Fahrenheit; Normal Operating Temperature up to 2,150 Degrees Fahrenheit; Car Can Hold up to 285,000 lbs; 12 Casted Alloy Supports; Workable Dimensions: 50' L x 11'-6" W x 7' H



50' OLSON INDUSTRIES Car Bottom Furnace

FOR FURTHER INFORMATION CONTACT: Nyk Westbrook at 818.738.0800 or email nwestbrook@maynards.com

SALE CONDUCTED BY:

Maynards
 SINCE 1902

AUCTIONS | LIQUIDATIONS | APPRAISALS

21700 Northwestern Hwy., Suite 1180
 Southfield, MI 48075

248.569.9781 | maynards.com

SALE IN CONJUNCTION WITH:

GALAXIE CORPORATION
 Worldwide Metalworking Equipment Dealer

NATIONAL MACHINERY EXCHANGE, INC.