

CRANE ASSEMBLY CLEARANCE DIMENSIONS

MAX WHEEL LOAD 57300 LB
 CRANE CAPACITY (MH)
 LIFT - MAIN HOIST ... 343.57 28' - 7.56"
 LIFT - AUX HOIST N/A N/A
 AVAILABLE LIFT MH ... 45' - 0.00"
 AVAILABLE LIFT AH ... N/A
 SPREAD 120.00 IN

75 *CHECK CAPACITY
 DECIMAL PLACES*

14-Dec-93

PACSETER CRANE - RE

A (SPAN) 1241.00 IN 103' - 5.00"
 B 91.95 IN 7' - 7.95"
 B1 N/A IN N/A
 C 6.87 IN 0' - 6.87"
 D 45.38 IN 3' - 9.38"
 D1 N/A IN N/A
 E 45.94 IN 3' - 9.94"
 F 108.38 IN 9' - 0.38"
 F1 N/A IN N/A
 G 44.63 IN 3' - 8.63"
 H 36.00 IN 3' - 0.00"
 J 28.38 IN 2' - 4.38"
 K 50.25 IN 4' - 2.25"
 L 96.00 IN 8' - 0.00"
 DIST DWN PLAT ANGLE . 50.00 IN
 48.67 in min , 68 in max
 M 192.00 IN 16' - 0.00"
 N 140.94 IN 11' - 8.94"
 O 92.09 IN 7' - 8.09"
 P N/A IN N/A
 Q 360.00 IN 30' - 0.00"
 R 95.00 IN 7' - 11.00"
 S 14.50 IN 1' - 2.50"
 T N/A
 U N/A
 V N/A
 W N/A
 X 80.00 IN 6' - 8.00"
 CAB HANGER/LADDER ...16A1085D1F1 80" < XDIM < 92"
 CAB HANGER/LADDER WT. 188 LB
 Y 112.50 IN 9' - 4.50"
 Y1 N/A IN N/A
 Z 112.50 IN 9' - 4.50"
 Z1 N/A IN N/A
 AA 35.00 IN 2' - 11.00"
 CC 72.00 IN 6' - 0.00"
 TT 1240.74 IN 103' - 4.74"

R-B CLEARANCE
 3.055 in-OK

CAB CLEARANCE
 target LDIM
 96 in
 -chg DDTA, XDIM
 as required

O DIMENSION
 79.78 MAIN H
 N/A AUX H
 92.09 SENSOR

S-C CLEARANCE
 7.63 in-OK

CRANE ASSEMBLY CLEARANCE DIMENSIONS

MAX WHEEL LOAD 57300 LB
 CRANE CAPACITY (MH)
 LIFT - MAIN HOIST ... 343.57 28' - 7.56"
 LIFT - AUX HOIST N/A N/A
 AVAILABLE LIFT MH ... 45' - 0.00"

75 *CHECK CAPACITY
 DECIMAL PLACES*