

This Drawing and its Contents are the Proprietary Property of BLISS CLEARING NIAGARA, INC. and may only be used fo the purpose it is provided for

PRESS STROKE ~ 10"
SLIDE ADJUSTMENT ~ 12"
PRESS SPEED 30-60 S.P.M.
GEAR RATIO 6.428 TO 1
FLYWHEEL 52½ O.D. ~ 10 RIM ~ 17 FACE
VAMCO BK2-20 CAM FEED
APPROX WT. 168,000 #

IMPORTANT NOTICE!
ALL GUARDS REMOVED TO FACILITATE SHIPPING MUST BE REPLACED PRIOR TO OPERATING MACHINE

WARNING
OSHA REQUIRES PROTECTION OF OPERATOR BY GUARDING POINT OF OPERATION. A POINT OF OPERATION GUARD IS NOT INCLUDED WITH THIS PRESS. IT IS TO BE PROVIDED BY THE EMPLOYER.

MAY 2 4 2004

UNIT # 1

REVISIONS	DESCRIPTIONS	DATE	BY
	58½ was 34⅝; ADD 23½ DIM ADD DETECTOR OUTLET	11-23-87	TECOMB

CONFIDENTIAL
THIS DRAWING, INCLUDES AS INFORMATION CONTAINED THEREON, IS THE EXCLUSIVE PROPRIETARY PROPERTY OF E. W. BLISS COMPANY, IT IS DESIGNED IN CONFIDENCE AND IS NOT TO BE RETAINED IN CONFIDENCE AND WILL NEITHER BE DUPLICATED OR COPIED IN WHOLE OR IN PART NOR DISCLOSED OR USED FOR PURPOSES OTHER THAN THAT FOR WHICH SUPPLIED

UNLESS OTHERWISE SPECIFIED
FRACTIONAL FINISH DIMENSIONS ± 1/64
DECIMAL FINISH DIMENSIONS ± .002

E.W. Bliss Company
HASTINGS, MICH. SALEM, OHIO

ORDER NO.	UNITS REQ'D.	TOTAL QUAN.	BREAK ALL SHARP EDGES
HP-53761			DR ATM 6-11-87

SC2-500 108x54 SG. T.E.D.
GENERAL PLAN
9650-D-1316

CH. —— SCALE 1/4" = 1"

MYLAR MADE FROM 9650-D-1276