


	A	B	C	D	D1
ST'D. BODY	120 5/8	154 3/4	171 1/2	161 3/4	62
HI-BODY	124 5/8	158 3/4	175 1/2	165 3/4	62

CAPACITY OF PRESS	150 TONS
STROKES PER MINUTE	
STROKE OF SLIDE	IN.
ADJ. OF SLIDE	.5 IN.
MAX. PRESS INCLINATION	25°
WEIGHT OF PRESS	39,000#

FINISH STANDARDS	
SYMBOL	FINISH, MICRO INCH
▽▽	1000 MAX.
▽	500 MAX.
/	250 MAX.
FLAT SURFACES	
/	63 MAX.
SHAFTING	
G	32 MAX.
▽▽	16 MAX.

TOLERANCE: ± .010 FOR ALL FRACTIONAL DIMENSIONS. .002 FOR ALL DECIMAL DIMENSIONS UNLESS OTHERWISE SPECIFIED.

O.S.T. STANDARD DWG. DO NOT ALTER WITHOUT APPROVAL OF CHIEF ENGINEER

FEB 07 200

CONFIDENTIAL & PROPRIETARY INFORMATION: This drawing and the information it contains are the property of Illinois Clearing Niagara, Inc. ("ICN") and are being provided upon the understanding and agreement between ICN and recipient that recipient will use them only for purposes specified and approved by ICN and will not use them for any other purposes, that recipient will not disclose them in any way to any individual or entity, other than recipient's agents or employees engaged in performing the purposes specified and approved by ICN, and that recipient will immediately return this drawing, any copies of it, and all documents containing information from it to ICN upon request. Recipient's acceptance of delivery of this drawing constitutes acceptance of these terms.

REVISIONS				ORIGINAL DWG. NO.	CODE 350
LET	DATE	REMARKS	BY		
A				USI	CLEARING
B					Division of U.S. INDUSTRIES, INC.
C					CANTON, OHIO 44707
D				GENERAL ASSEMBLY	
E				150 TON D.R.I. PRESS	
F					
G					
H					
J					