



467 1/2 (38 FT. 11 1/2 IN.)

400 3/4 (33 FT. 4 3/4 IN.)

383 1/4 (32 FT. 9 3/4 IN.)

CUSTOMER TO PROVIDE ALL NECESSARY SAFETY BARRIERS

192 (16 FT.)

60

91

36 7/16

36 7/16

24

133 1/2 SWING DIA.

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18

19

3 3/4

46 1/2

50 1/4

18

19

38

192

60

24

91

36 7/16

36 7/16

74

43

113 APPROX.

72 O.D. MAX.

41 5/8

36 O.D. MINIMUM RESTRICTION

37

18