

# PRECISION METAL LATHES

22-4

## DIMENSIONS AND SPECIFICATIONS 22-4 PRECISION METAL LATHE

SPECIFIC ATIONS



| SPECIFICATIONS                      | 22-4                 |
|-------------------------------------|----------------------|
| CAPACITIES                          |                      |
| Swing Over Bed                      | 22"                  |
| Swing Over Cross Slide              | 12 1/2"              |
| Swing Over Gap                      | 32"                  |
| Length of Gap                       | 8"                   |
| HEADSTOCK                           |                      |
| Spindle Bore                        | 4 1/8"               |
| Spindle Speeds - number             | 12                   |
| Spindle Speeds - range              | 35 - 1250 RPM        |
| Spindle Nose                        | D1 - 8               |
| FEEDS & THREADS                     |                      |
| Threads per inch - (number) range   | (36) 2 - 28 TPI      |
| Metric Threads - (number) range     | (65) .8 - 14         |
| Longitudinal Feeds - (number) range | (23) .001"027" IPR   |
| Cross Feeds - (number) range        | (23) .0005"0135" IPR |
| Leadscrew - (diameter) range        | (1 3/4") 2 TPI       |
| CARRIAGE & APRON                    |                      |
| Cross Slide Travel                  | 14 3/4"              |
| Compound Travel                     | 10"                  |
| TAPER ATTACHMENT                    |                      |
| Degrees of Taper                    | +/- 10 degrees       |
| Length of Taper Per Setting         | 16"                  |
| BED                                 |                      |
| Width of Bed                        | 16"                  |
| Bed Way Hardness (Rockwell C)       | 44 - 50              |
| TAILSTOCK                           |                      |
| Travel of Spindle Barrel            | 6 1/2"               |
| Diameter of Spindle Barrel          | 3"                   |
| Taper of Center                     | #5 MT                |
| MOTORS                              |                      |
| Spindle motor                       | 15 HP                |
| Coolant Pump                        | 1/4 HP               |
| MISCELANEOUS                        |                      |
| Width x Height                      | 36" x 54"            |
| Length/Weight - 60"                 | 123" / 6,380 lbs.    |
| Length/Weight - 80"                 | 143" / 7,150 lbs.    |
| Length/Weight - 120"                | 183" / 8,800 lbs.    |
| Length/Weight - 160"                | 223" / 10,670 lbs.   |



#### **INCLUDED ACCESSORIES**

- · 3 jaw chuck
- 4 jaw chuck
- · Steady rest
- · Follow rest
- Full-length splash guard
- · Halogen work light
- Taper attachment
- Coolant system
- Thread dial
- · Micrometer carriage stop

#### STANDARD FEATURES

- · Inch and metric threading
- · Hardened & precision ground bedways
- · Removable gap
- · T-slotted compound
- · All cast iron construction
- · Clutched headstock
- Dual dials inch/metric
- Dual voltage 220/440 volt / 3 phase / 60 Hz
- Two speed tailstock
- Four-way rapid traverse

WARRANTY: A copy of Summit Machine Tool LLC's standard written warranty is attached to each Summit Machine. Call or write to Summit for a copy or for further information concerning Summit's standard warranty. All purchases are subject to Summit's standard written warranty. Specifications are subject to change without notice.

**POINT OF OPERATION GUARDING** is the responsibility of the end user. For information contact your local OSHA office.

### **SUMMIT MACHINE TOOL LLC**

518 N Indiana Ave • Oklahoma City, OK 73106

MAIN 405.235.2075 FAX 405.232.5169



FOR MORE INFORMATION CALL 1-800-654-3262
WWW.SUMMITMACHINETOOL.COM