
RICHARDS Multiform

HYDRAULIC UTILITY BENDER

AVAILABLE

OPERATES IN EITHER HORIZONTAL OR VERTICAL POSITION



Patent pending Any OSHA guarding requirements are the responsibility of the purchaser

CAPACITY

1/2" x 4" mild steel 5/8" x 3" mild steel 3/4" x 2" mild steel 1-1/2" round mild steel 1-1/2" square mild steel 2" schedule 40 pipe 1/4" x 2" mild steel angles Notching: 1/4" x 2" angle mild steel 2" schedule 40 pipe Piercing: 1/2" holes, 1/4" mild steel Shearing: 1/4" x 4" mild steel Rod Parting: 1/2" mild steel

© copyright 1982

903 N. Pitcher St., Kalamazoo, Michigan 49007 616/343-4684 • Toll Free 1-800-253-3288 • TWX 810-277-1020 Mich. 1-800-632-4162

Manufactured in U.S.A.



CATALOG 74A MODEL MUB FACTORY NO: MUB001 without tooling

THE MOST VERSATILE ALL PURPOSE UTILITY BENDER

FLAT BENDING • PIPE BENDING • ROD BENDING • U-BOLTS • REBAR • **BUSS BARS • TOOLING AVAILABLE FOR SPECIAL SHAPES AND DESIGNS**



am travel:	12″
Rating:	10 Tons
Power:	2 HP, 220V-1 Phase, 220V-3 Phase
	440V-3 Phase, (Specify)
	5HP Gasoline Engine (optional)
aceplate:	12" x 30"
Working Height:	Horizontal 39"
	Vertical 36"
Height:	42" (Horizontal)
Width:	30″
Depth:	42"
Shipping Weight:	500 lbs.

J.A.RICHARDSCOMPANY

Printed in U.S.A.

RICHARDS

- DOVETAIL TOOLING AVAILABLE
- VARIABLE SPEED RAM
 - RAM STROKE ADJUSTABLE
 - ROTARY BENDER ATTACHMENT (Optional) See catalog No. 75



1" ROUND U BOLT



FLAT BENDING 1/2" x 4" hot roll



HORIZONTAL MODE


Forming 2"

schedule 40 pipe



 \bigcirc


2" PIPE BENDING



1-1/4" PIPE BENDING



1" ROUND BENDING



ROD PARTER 1/2" Mild Steel



Dovetail Adapters with Standard Tooling 1/4" x 4" Hot Roll (as used on our standard benders)




ROTARY BENDING ATTACHMENT

- UNIQUE AND EXCLUSIVE BENDING ATTACHMENT
- MOUNTS TO BENDER FACEPLATE (EASY TO INSTALL AND REMOVE)
- ECONOMICAL AND HIGHLY VERSATILE TOOLING AVAILABLE
- POPULAR SIZE TOOLING SETS AVAILABLE FROM INVENTORY


MUB080 ATTACHMENT SHOWN MOUNTED ON MUB UTILITY BENDER





 $\mathbf{\nabla}$





CAPACITY

- 1-1/4" 16 ga. Tubing 3/4" Round Mild Steel 1/2" Square Mild Steel 3/4" Rebar 3/4" Schedule 40 Pipe 1/4" x 2" Mild Steel (flat) 1/2" Round Mild Steel (Double Bend)
- 1/4" x 1" Mild Steel (Edge)

© copyright 1982



Manufactured in U.S.A.



MODEL NO. RBA001

FACTORY NO. MUB080 FOR MUB FACTORY NO. RBA002 FOR BBC FACTORY NO. RBA003 FOR 44HB, **BBB & BBH** (patent pending)

FITS HYDRAULIC RAM BENDER MODELS: MUB - 44HB - BBB - BBC - BBH

• BEND TUBING, ROUNDS, SQUARES AND FLATS EASILY AND QUICKLY WITH THIS

J.A.RICHARDSCOMPANY


903 N. Pitcher St., Kalamazoo, Michigan 49007 616/343-4684 • Toll Free 1-800-253-3288 • TWX 810-277-1020 Mich. 1-800-632-4162


Printed in U.S.A.

RICHARDS

TOOLING SETS FOR TUBE BENDING

(Tooling set consists of form block with hook clamp and form bar)






PART NO.	TUBING OD	RADIUS	NOMENCLATURE	
RBA095	.250	.75CLR*	Tooling Set	
RBA096	.312	.93CLR	Tooling Set	
RBA097	.375	1.12CLR	Tooling Set	
RBA098	.500	1.50CLR	Tooling Set	
RBA099	.625	1.87CLR	Tooling Set	
RBA100	.750	2.25CLR	Tooling Set	
RBA101	.875	2.62CLR	Tooling Set	
RBA102	1.000	3.00CLR	Tooling Set	
RBA103	1.125	3.37CLR	Tooling Set	
RBA104	1.250	3.75CLR	Tooling Set	
RBA105	1.375	4.12CLR	Tooling Set	
RBA106	1.500	4.50CLR	Tooling Set	

Form Bar (Tube Bending Tooling sets for MUB080 Attachment also fit Models 3 & 3P Rotary Benders)

ACCESSORIES FOR TUBE BENDING




Bar Clamp is required with first set of tooling


RADIUS FORM BLOCKS FOR BENDING RODS, SQUARES, FLATS OR REBAR (RBA110 Bend Set Required) (Roller Bend Pins Required)

Radius	PART NO.	RADIUS	PART NO.	RADIUS	PART NO.	RADIUS
	RBA114	1″	RBA121	2-3/4"	RBA128	4-1/2"
$\left(\circ \right)$	RBA115	1-1/4 "	RBA122	3″	RBA129	4-3/4"
	RBA116	1-1/2"	RBA123	3-1/4"	RBA130	5″
	RBA117	1-3/4 "	RBA124	3-1/2"	RBA131	5-1/4"
	RBA118	2"	RBA125	3-3/4"	RBA132	5-1/2"
	RBA119	2-1/4"	RBA126	4 "	RBA133	5-3/4"
Form Block	RBA120	2-1/2."	RBA127	4-1/4 "	RBA134	6″

ACCESSORIES FOR BENDING RODS, SQUARES, FLATS OR REBAR Bend Set consists of two Bend Bars and one Swing Arm



Bend Set



RBA110

Note: Two to five roller bend pins required with first Bend Set (number depends on type of bend required)

HAD

RIC

J. A. Richards Company provides engineering and fabrication service for special tooling designs for all cataloged models. Designs and specifications subject to change without notice.

Roller Bend Pin

- FUNCTIONS AS ARBOR PRESS


 - SENSAMATIC CONTROL VALVE
 - DEADMAN CONTROL



VERTICAL MODE STRAIGHTENING PRESS Flat or round, etc.



PIERCING 1/2" x 1/4"




TUBING NOTCHING






PIERCING, SHEARING, NOTCHING AND ROD PARTING ATTACHMENTS (Optional)




RICHARDS




RICHARDS

BENDING GATE FRAME FOR LIVE STOCK PEN


Bending gate frame for live stock pen on the Utility Bender to form 7" inside radius with 18" between the legs. Material is 1" square 12 gauge tubing.







item 2

WING DIE TOOLING IS USED TO BEND 1-1/2 HR U-BOLTS Wing die tooling used to bend 1-1/2'' hot rolled "U" bolts.





Marine radar tower and canopy made on the Utility Bender.




RICHARDS


Edge bending $1/4 \times 4$ copper.


BENDING HANDLE BAR FOR EXERCISE MACHINE

Bending handle bar for exercise machine. Forming of the 6" radius on the rotary tooling attachment. Forming the large radius in three hits, using ligniform tooling material for the punch section is shown in illustration 1.



ROTARY BENDING ATTACHMENT FOR HYDRAULIC RAM BENDERS Rotary bending attachment for hydraulic or pneumatic ram benders with particular applications as shown for the Utility Bender with a longer stroke.






Crush bending 1-1/4" square 16 gauge stainless on a 44HB or BBB Model Bender.

Page 5







item 5

Crush bend tooling used on the Utility Bender for large diameter radius. Crush bend forming of guard rails for livestock pen applications.



Page 6