



## **Technical Specifications**

Rectangular Capacity

0-12.75" W x 0-12.75" H

**Square Capacity** 

0-12" (Square)

**Round Capacity** 

0-12.75" (Diameter)

**Bar-feed** 

0-24" (Stroke Air - Single

Index)

Motor

3 HP

**Hydraulic Motor** 

N/A

**Operation Type** 

Automatic

**Power Source** 

Air

Weight

N/A

**Blade Type** 

Bandsaw

**Blade Size** 

12' 10" L x 1" H x .035"

Cantilever

**Bandsaw Blade** 

Speed

N/A

**Bundle Cut?** 

Yes

## **Optional Features**

Vise - 3rd on Feed Top Clamp - Reduced Capacity Main Vise Light Clamping Pressure Spray Mist Lubrication

### **Product Description**

**Horizontal Pivot Band Saws** 

> Non-Miter Horizontal Pivot Saws

>> H90 Series

The H90A-1 offers accurate cuts on small solids and shapes. It is perfect for cutting multiple parts of the same length up to 24" long automatically. This simple to use scissor-type band saw has a long track record for years of reliable service.

#### **Standard Features**

Control Console on Top of Saw - Bi-Function Control

18" Discharge Support

Vise - Adjustable Main & Feed

Adjustable Clamping Force

2 Hold Down Fixtures

Guide Arm - Manual Adjustment

Variable Blade Speed w/ LED Readout

Carbide Blade Guides

Manual Blade Tension

Adjustable Feed Rate

Adjustable Cutting Pressure

Coolant System - Flood w/ Wash-Down Hose

Vertical Alignment Bar on Bar-Feed

Blade Brush

**Broken Blade Function** 

**Out-of-Stock Function** 

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

85 PSI, 4-6 CFM Minimum Air Requirement

(Equipped w/ Air Filter/Lubricator)

Interlocking Vise Jaws
Top Clamp - Reduced Capacity Feed Vise
24" Solid Discharge Table
5' Idle Roller Stock Table

# **HEMSAW.COM**

1 (888) 729-7787