

Utility Band Saw



For larger material that requires a band saw, this scaled-down but rugged horizontal band saw can easily cut through round material up to 8" diameter, & features a swing head that can miter 60° right of 90°, giving you a 30° cut part without material movement.

BAND SAW



Optional Conveyor and measuring devices available

STANDARD FEATURES

- Quick action locking vise
- Miter Capability 60° right of 90°
- Blade trigger switch
- Gravity feed with adjustable down-feed pressure
- Blade tension gauge
- Carbide blade guides with roller supports
- Re-circulating coolant system
- Band door interlocks
- One saw blade
- One gallon coolant
- Meets CE standards
- Three-year warranty on parts
- Made in Spain

OPTIONAL EQUIPMENT

- Conveyor (10' and 20')
- Manual or digital measuring system (see pages 43-44)

SU-280 G

SPECIFICATIONS

Blade Length	1" x 96.5" (25 x 2,451 mm)
Two Cutting Speeds	131/262 FPM (3 phase machines)
One Cutting Speed	196 FPM (1 phase machines)
Motor Options (must specify)	1.3 hp (1kW) 3ph, 230/460v 1ph, 220v
Width	33-1/2" (85 cm)
Depth	55" (140 cm)
Height	69" (175 cm)
Shipping Weight (may vary)	650 lbs. (295 kg)



MAXIMUM CAPACITIES

Tubing	90 Degree	45 Degree	60 Degree
Round	8" (203 mm)	7" (178 mm)	4-1/4" (108 mm)
Square	8" (203 mm)	6-1/4" (159 mm)	4" (102 mm)
Rectangle	11" x 7-3/4" (279 x 197 mm)	7" x 6-1/4" (178 x 159 mm)	4-1/4" x 4" (108 x 102 mm)