

MATAWAY® OVERSEEDER



TRUST RYAN®

Heavy-duty and built to perform, the Mataway Overseeder places seeds directly into soil slits for fast germination and unmatched seed-to-soil contact, aeration, and overseeding.

OVERSEEDER FEATURES

- 1. OVERSEED WITH CONFIDENCE**
Seed flow rate is easily controlled right from the operator's station and stops automatically when the reel is raised.
- 2. ADJUSTABLE CUTTING BLADES & SEED DEPTH GUIDE**
Adjust durable cutting blades down to a depth of 0.25" while seeding at variable rates for different grass varieties and applications.
- 3. MAXIMUM GERMINATION**
The curve-shaped discs place seeds directly into soil slits for unmatched seed-to-soil contact.



SEED DEPTH GUIDE



SIMPLE OPERATION



ULTIMATE SEED-TO-SOIL CONTACT AND MAXIMUM GERMINATION



FOR MORE INFORMATION, VISIT RYANTURF.COM

MATAWAY® OVERSEEDER SPECIFICATIONS



HONDA® Engine Model	<ul style="list-style-type: none"> 4-cycle Honda® GX390 Recoil start On/off switch Low-oil alert
Displacement	23.7 cu in. (389 cc)
Fuel Capacity	1.6 gal (6.1 L)
Oil Capacity	1.16 qt (1.1 L)
Clutch	Spring-loaded belt tightener
Drive	<ul style="list-style-type: none"> 4L-section V-belt to front wheels by gear box and sealed roller chain Triple 3V-section V-belts engine to reel
Tires	<ul style="list-style-type: none"> Front: (2) 4.10/3.50 x 4, 2-ply pneumatic, knob tread Rear: (2) 4.10/3.50 x 4, 2-ply pneumatic, sawtooth tread
Operating Width	19 in. (483 mm)
Cutting Depth	Seeding and Fixed Blades: Up to 0.25 in. (6 mm) below ground
Blade Adjustment	Micrometer screw; adjustable up to 1.25" (32 mm) for blade wear
Seeding Blade	(10) 8-point, high carbon, heat treated blades, 2 in. (51 mm) spacing
Flail Blade Type	Hardened, high-carbon steel blades: 1/8 in. (3 mm) at 1 in. (25 mm) spacing
Fixed Blade Type	Hardened, high-carbon steel blades: <ul style="list-style-type: none"> 1/32 in. (1 mm) at 1/2 in. (13 mm) spacing 1/32 in. (1 mm) at 1 in. (25 mm) spacing 1/16 in. (2 mm) at 1 in. (25 mm) spacing 1/16 in. (2 mm) at 1 1/2 in. (38 mm) spacing
Weight: Wet	453 lb (205 kg) w/o reel
Width	35.5 in. (902 mm)
Length	50 in. (1,270 mm)
Height	44 in. (1,118 mm)
Lubrication	Oil splash in gear case, grease fittings elsewhere
Productivity	<ul style="list-style-type: none"> Single Pass: 80%; 18,700 sq ft/hr Double Pass: 80%; 9,400 sq ft/hr

FOR MORE INFORMATION,
VISIT RYANTURF.COM

One Bobcat Lane | Johnson Creek, WI 53038-0469
For more information about RYAN® products, visit your RYAN® dealer today. For the location of the dealer nearest you, call 866-469-1242 or visit www.ryanturf.com.

©2022 Clark Equipment Co. All Rights Reserved.



TRUST RYAN®