



MODEL AS375-12 SHEAR

CAPACITY (TO MILD STEEL)	3/8" x 12'
SHEARING TONS AVAILABLE	60
RAKE (IN INCHES PER FOOT)	.4"
SHIPPING HEIGHT/WIDTH/DEPTH (w/36" travel)	100"x 174"x 90"
NUMBER OF HOLD DOWN CYLINDERS	13
BORE OF HOLD DOWN CYLINDERS	2"
HOLD DOWN TONS OF FORCE	48
BLADE SIZE	1"x3"x148"
WEIGHT (U.S. LBS.)	30,000
HORSEPOWER STROKES PER MINUTE:	30
FULL WIDTH CUT	9
12" WIDE CUT	30
BELOW GRADE	no
RAM SPEED IN INCHES PER MINUTE-DOWN	125
RAM SPEED IN INCHES PER MINUTE-UP	178



Features Include:

- ★ All Components Readily Available from Your Local Suppliers
- ★ Precision Guillotine Drive Providing the Best Shearing System Available
- ★ Super heavy duty, 36" travel, precision ball screw backgauge with 500 IPM travel speed.
- ★ Highly visible, LED shadow lights for shearing line
- ★ Backgauge includes manual swing-away backstop, programmable X-retract and up to 200 programmable jobs via Cybelec control.
- ★ Manual, side adjustable, quick-change blade gap adjustment
- ★ Off the shelf Cybelec shear control with 200 job programmability
- ★ 80,000 PSI Capacity rated
- ★ 5 Year Parts Warranty
- ★ 5 Year limited onsite labor warranty
- ★ UL508A Compliant
- ★ Manifold centralized lubrication system
- ★ Lifetime telephone support at no charge
- ★ 4' squaring arm with scale
- ★ (2) Hand slots in the table
- ★ (2) T-slots in shear table
- ★ T-slot across front edge of shear table

AS375-12 w/features listed for \$112,500.00

(fob Clarksdale, MS)