



Model 7400 Specifications

INDUSTRIAL RIDING SCRUBBER

Feature	English	Metric
Scrubbing System		
Cleaning path with side brush without side brush	57-inch 45-inch	1450 mm 1145 mm
Solution tank	70 gallon	265liter
Cylindrical scrub head Speed Down pressure weight (variable to) Brush diameter (2) Brush length (2)	400 rpm 400 lb 11-inch 45-inch	400 rpm 180 kg 280 mm 1145 mm
Optional side brush Speed Down pressure weight (variable to) Brush diameter (2)	210 rpm 140 lb 16-inch	210 rpm 65 kg 405 mm
Recovery System		
Recovery tank Demisting chamber	70 gallon 34 gallon	265 liter 129 liter
Vacuum fan speed	14,000 rpm	14,000 rpm
Vacuum water lift	45-inch	1145 mm
Propelling System		
Propel speed forward (variable to)	8.0 mph	12.9 km/h
Propel speed reverse (variable to)	4.0 mph	6.4 km/h
Engine-gasoline/LPG	55 hp GMC	41 kW GMC
Engine-diesel	37.5 hp Kubota	28 kW Kubota
Gradeability Transport at gross weight Working (scrubbing)	8 deg/14.1% 6 deg/10.5%	8 deg/14.1% 6 deg/10.5%
Machine Dimensions		
Length	97-inch	2465 mm
Width With optional side brush Rear squeegee	60-inch 63-inch 60-inch	1525 mm 1600 mm 1525 mm
Height With overhead guard	58-inch 80.5-inch	1475mm 2045 mm
Weight	3,299 lb	1495 kg
Minimum aisle turn	125.5-inch	3185 mm
Warranty	24 months/2,000 hours on parts 6 months labor 5 years/5,000 hours Duramer™ tanks	