



MINSTER E2-600-84 X 48	PRESS
CAPACITY	600 TONS
STROKE	12 INS.
ADJUSTMENT	6 INS.
STROKES PER MINUTE	0 TO 60 S.P.M.
USABLE ENERGY @ 30 S.P.M.	= 175 IN TONS
MAX. USABLE ENERGY	FROM 39 TO 60 S.P.M. = 286 IN. TONS

NOTE: PRESS MAY BE SINGLE STROKED AS NOTED BELOW. A HIGHER RATE OF SGL. STROKING MAY CAUSE EXCESSIVE MAINTENANCE OF CLUTCH & BRAKE.

CONTINUOUS SPM	SGL. STROKE SPM
30	20
45	10
60	6

INCLUDES EXHAUST MUFFLER ON CLUTCH VALVE.

INCLUDES AIR OPERATED FLYWHEEL BRAKE ELECTRICALLY INTERLOCKED WITH MAIN MOTOR STOP CIRCUIT.

INCLUDES WINTRESS COMBINATION DIE PROTECTION AND LOAD ANALYZER UNIT. (STRAIN LINKS MOUNTED ON R.H. FRONT AND L.H. REAR UPRIGHTS)

EST. WEIGHT	RAW MATERIAL WEIGHT	MACHINED SURFACES UNLESS OTHERWISE SPECIFIED	THE MINSTER MACHINE CO.		LAST REV. DATE
GROUP TECH NO	E2-600-84-2000-001	DIMENSION TOLERANCE I	MINSTER, OHIO	REV. LEVEL	CHANGED BY
REFERENCE NO		X AND X X 0 1.00	<small>© 1987 THE MINSTER MACHINE COMPANY. THIS DOCUMENT IS THE EXCLUSIVE PROPERTY OF THE MINSTER MACHINE COMPANY. ANY DISCLOSURE, DISTRIBUTION AND/OR REPRODUCTION WITHOUT THE EXPRESS WRITTEN CONSENT OF THE MINSTER MACHINE COMPANY IS PROHIBITED. ALL RIGHTS RESERVED.</small>		
SUPERSEDED BY		X XXX 0 0.01			
SUPERSEDES		X XXXX 0 0.005			
PATTERN FILE NO		FINISH 125 MICROINCHES			
PATTERN BASIC NO		BREAK SHARP CORNERS 0.03	DATE	DRAWN BY	CHECKED BY
		[1] [015] [Z] [015] [/] [015]	7-10-87	FJW	AHRNS
			SCALE		
			GENERAL ASSEMBLY (LIMITED EDITION)		
			MATERIAL	PART NO	
			NO	REV'D	D
			PART NO	1152-573	