



MODEL AB400-14 SPECIFICATIONS

TONNAGE FORMING/PUNCHING	400/260
DISTANCE BETWEEN HOUSINGS	12'-5"
BED/RAM LENGTH	14'
BELOW GRADE	NO
WEIGHT (<i>LBS.</i>)	68,000
BED HEIGHT	40"
BED WIDTH	14"
OVERALL HEIGHT	148"
THROAT DEPTH	10"
RAM STROKE (<i>FULLY ADJUSTABLE</i>)	10"
OPEN HEIGHT (<i>MAXIMUM HEIGHT</i>)	20"
CLOSED HEIGHT (<i>MINIMUM HEIGHT</i>)	10"
HORSEPOWER	40**
RAM SPEEDS (<i>IN INCHES PER MINUTE</i>)	
APPROACH	110
PRESS	17
RETURN	106

**460/480 voltage only unless w/special quote

MADE IN THE U.S.A



Features Include:

- ★ Off The Shelf, Readily Available from Your Local Suppliers
- ★ Power ram tilt
- ★ Groove in Bed and Ram Clamps for American Style Tooling
- ★ Perfect for full length and off-center loading applications
- ★ Full Tonnage across Bed and Ram
- ★ Full Tonnage throughout Stroke
- ★ Simple limit switch ram control (CNC optional)
- ★ Counterbalance for Punching applications
- ★ UL508A compliant
- ★ Typical +, - .001" Repeatability
- ★ 5 Year Parts Warranty + 5 Year Limited Onsite Labor Warranty
- ★ Lifetime Telephone Support at No Charge
- ★ (2) 24" Work Support Arms
- ★ Manifold centralized lube system
- ★ Hand/Foot sequence w/footswitch
- ★ T-slot across front edge of brake bed

AB400-14 w/features listed above for \$201,500.00

(fob Clarksdale, MS)

MADE IN THE U.S.A