



MODEL AB600-20 PRESS BRAKE

TONNAGE FORMING/PUNCHING	600/420
DISTANCE BETWEEN HOUSINGS	18'-5"
BED/RAM LENGTH	20'
BELOW GRADE	yes
WEIGHT (<i>LBS.</i>)	150,000
OVERALL HEIGHT (<i>Approx.—reduces w/pit depth</i>)	170"
BED WIDTH	14"
BED HEIGHT (will require full machine pit)	contact factory
THROAT DEPTH	10"
RAM STROKE (<i>FULLY ADJUSTABLE</i>)	10"
OPEN HEIGHT (<i>MAXIMUM HEIGHT</i>)	22"
CLOSED HEIGHT (<i>MINIMUM HEIGHT</i>)	12"
HORSEPOWER	50
RAM SPEEDS (<i>IN INCHES PER MINUTE</i>)	
APPROACH	60
PRESS	15
RETURN	125

MADE IN THE U.S.A.



Features Include:

- ★ Off The Shelf, Readily Available from Your Local Suppliers
- ★ Power ram tilt
- ★ Groove in Bed and Ram Clamps for American Style Tooling
- ★ Perfect for full length and off-center loading applications
- ★ Full Tonnage across Bed and Ram + Full Tonnage throughout Stroke
- ★ Simple limit switch ram control (CNC optional)
- ★ Counterbalance for Punching applications
- ★ UL508A compliant
- ★ Typical +, - .001" Repeatability
- ★ 5 Year Parts Warranty + 5 Year Limited Onsite Labor Warranty
- ★ Lifetime Telephone Support at No Charge
- ★ (4) 24" Work Support Arms
- ★ Manifold centralized lube system
- ★ T-slot across front edge of brake bed
- ★ Hydraulic Tonnage Control
- ★ Hand/Foot sequence w/Footswitch with (2) pedestal and (2) footswitch stations for up to 2 operators

AB600-20 w/features listed above \$404,900.00

(fob Clarksdale, MS)

MADE IN THE U.S.A