

MODEL AS250-14 SHEAR

CAPACITY <i>(TO MILD STEEL)</i> CAPACITY <i>(TO STAINLESS STEEL)</i>		¼" x 14' 10 ga x 14'
SHEARING TONS AVAILABLE		36
RAKE (IN INCHES PER FOOT)		.250"
SHIPPING HEIGHT (approx.)		105"
WIDTH		200"
DEPTH		88"
NUMBER OF HOLD DOWN CYLINDERS		15
BORE OF HOLD DOWN CYLINDERS		2"
HOLD DOWN TONS OF FORCE		40
BLADE SIZE		1"x4"x172"
WEIGHT (U.S. LBS.)		36,000 lbs.
HORSEPOWER		25
	PER MINUTE: FULL WIDTH CUT 12" WIDE CUT	12 40
BELOW GRADE		no



Features Include:

- ★ All Components Readily Available from Your Local Suppliers
- ★ Precision Guillotine Drive Providing the Best Shearing System Available
- ★ Super heavy duty, 36" travel, precision ball screw backgauge with 400 IPM travel speed.
- ★ Highly visible, LED shadow lights for shearing line
- ★ Backgauge includes manual swing-away backstop, programmable X-retract and up to 200 programmable jobs via Cybelec control.
- ★ Automatic blade positioning with Infinitely Variable Power Blade Gap Adjustment.
- ★ Off the shelf Cybelec shear control with 200 job programmability
- ★ 80,000 PSI Capacity rated
- ★ 5 Year Parts Warranty
- **★** 5 Year limited onsite labor warranty
- ★ Manifold centralized lubrication system
- **★** UL508A Compliant
- ★ Lifetime telephone support at no charge
- ★ Heavy duty ball transfers in table
- ★ 4' squaring arm with scale
- ★ (3) Hand slots in the table
- ★ (2) T-slots in shear table
- **★** T-slot across front edge of shear table

AS250-14 w/all features listed for \$133,500.00

(fob Clarksdale, MS)