

MCR SERIES

The MCR Series is perfect for small diameter applications ranging from 0.050" to 0.315" (1.3mm - 8.0mm). With exceptional capstan life and improved tooling life, these machines have an air brake, manual clamp roller and spring compensator to provide precision control.

STANDARD FEATURES

- Patented one-way clutch wire relaxer roll
- Axial movement of wire relaxer for exit wrap alignment
- Durable through-hardened D2 tool steel capstan
- Full capstan cover with electrical interlock allowing full access to capstan
- Gripper chain
- Two hand jogging with all operator controls
- STARTGARD (production machine interlock)
- SLIPGARD (forward compensator over travel switch)
- TANGLEGARD (production machine interlock)

OPTIONS & ACCESSORIES

- Reverse frame (left to right wire flow)
- Twelve o'clock clamp roller
- End of coil detector
- Annular roller assembly
- 9" (228.0mm) Aluminum compensator wheel
- Remote grease points
- Pointer tooling
- Operator pendant control
- Exit wire guide assembly
- M1010A Huskie cutter
- HMI/touch panel
- Advanced diagnostics package
- Maintenance management schedule
- Alarm history

MODELS

MODEL 200

Capstan Diameter: 10" (255.0mm)
Maximum Diameter after draw: 0.100" (2.5mm)
Speed Range: 5 - 45FPM (1.5 - 13.5MPM)

MODEL 500

Capstan Diameter: 20" (500.0mm)
Maximum Diameter after draw: 0.315" (8.0mm)
Speed Range: 5 - 100FPM (1.5 - 30.5MPM)

