

310-5-48 Capacity Chart

Base Capacity		0.21	Top roll diameter		5	Working Length		48	Solving for Material Width in Inches		
									One Pass Rolling!		
Plate Thickness →		14ga	12ga	10ga	8ga	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"
Yield Strength PSI ↓	ID (in) ↓	0.0747	0.1046	0.1345	0.1644	0.1875	0.25	0.3125	0.375	0.4375	0.5
30,000	5.5	48.00	48.00	48.00	37.59	28.90	16.26	5.20	3.61	2.65	2.03
	6	48.00	48.00	48.00	44.12	33.92	19.08	6.11	4.24	3.12	2.38
	6.25	48.00	48.00	48.00	48.00	39.34	22.13	7.08	4.92	3.61	2.77
	7.5	48.00	48.00	48.00	48.00	48.00	28.90	18.50	6.42	4.72	3.61
	8.75	48.00	48.00	48.00	48.00	48.00	28.90	18.50	6.42	4.72	3.61
	10	48.00	48.00	48.00	48.00	48.00	36.58	23.41	16.26	5.97	4.57
	12.5	48.00	48.00	48.00	48.00	48.00	39.06	25.00	17.36	6.38	4.88
	15	48.00	48.00	48.00	48.00	48.00	40.76	26.08	18.11	6.65	5.09
	17.5	48.00	48.00	48.00	48.00	48.00	43.37	27.76	19.28	7.08	5.42
	20	48.00	48.00	48.00	48.00	48.00	45.16	28.90	20.07	7.37	5.64
	25	48.00	48.00	48.00	48.00	48.00	48.00	32.47	22.55	16.57	6.34
	30	48.00	48.00	48.00	48.00	48.00	48.00	33.71	23.41	17.20	6.58
40,000	40	48.00	48.00	48.00	48.00	48.00	48.00	35.61	24.73	18.17	6.95
	50	48.00	48.00	48.00	48.00	48.00	48.00	38.22	26.54	19.50	7.47
	5.5	48.00	48.00	42.12	28.20	21.68	6.10	3.90	2.71	1.99	1.52
	6	48.00	48.00	48.00	33.09	25.44	7.15	4.58	3.18	2.34	1.79
	6.25	48.00	48.00	48.00	38.38	29.50	16.60	5.31	3.69	2.71	2.07
	7.5	48.00	48.00	48.00	48.00	38.54	21.68	6.94	4.82	3.54	2.71
	8.75	48.00	48.00	48.00	48.00	38.54	21.68	6.94	4.82	3.54	2.71
	10	48.00	48.00	48.00	48.00	48.00	27.43	17.56	6.10	4.48	3.43
	12.5	48.00	48.00	48.00	48.00	48.00	29.29	18.75	6.51	4.78	3.66
	15	48.00	48.00	48.00	48.00	48.00	30.57	19.56	6.79	4.99	3.82
	17.5	48.00	48.00	48.00	48.00	48.00	32.53	20.82	7.23	5.31	4.07
	20	48.00	48.00	48.00	48.00	48.00	33.87	21.68	7.53	5.53	4.23
50,000	25	48.00	48.00	48.00	48.00	48.00	38.05	24.36	16.91	6.21	4.76
	30	48.00	48.00	48.00	48.00	48.00	39.50	25.28	17.56	6.45	4.94
	40	48.00	48.00	48.00	48.00	48.00	41.73	26.71	18.55	6.81	5.22
	50	48.00	48.00	48.00	48.00	48.00	44.79	28.67	19.91	7.31	5.60
	5.5	48.00	48.00	33.70	22.56	17.34	4.88	3.12	2.17	1.59	1.22
	6	48.00	48.00	39.55	26.47	20.35	5.72	3.66	2.54	1.87	1.43
	6.25	48.00	48.00	45.87	30.70	23.60	6.64	4.25	2.95	2.17	1.66
	7.5	48.00	48.00	48.00	40.10	30.83	17.34	5.55	3.85	2.83	2.17
	8.75	48.00	48.00	48.00	40.10	30.83	17.34	5.55	3.85	2.83	2.17
	10	48.00	48.00	48.00	48.00	39.02	21.95	7.02	4.88	3.58	2.74
	12.5	48.00	48.00	48.00	48.00	41.66	23.43	7.50	5.21	3.83	2.93
	15	48.00	48.00	48.00	48.00	43.47	24.45	7.83	5.43	3.99	3.06
60,000	17.5	48.00	48.00	48.00	48.00	46.26	26.02	16.65	5.78	4.25	3.25
	20	48.00	48.00	48.00	48.00	48.00	27.10	17.34	6.02	4.42	3.39
	25	48.00	48.00	48.00	48.00	48.00	30.44	19.48	6.77	4.97	3.81
	30	48.00	48.00	48.00	48.00	48.00	31.60	20.23	7.02	5.16	3.95
	40	48.00	48.00	48.00	48.00	48.00	33.38	21.37	7.42	5.45	4.17
	50	48.00	48.00	48.00	48.00	48.00	35.83	22.93	7.96	5.85	4.48
	5.5	48.00	46.43	28.08	18.80	7.23	4.06	2.60	1.81	1.33	1.02
	6	48.00	48.00	32.96	22.06	16.96	4.77	3.05	2.12	1.56	1.19
	6.25	48.00	48.00	38.22	25.58	19.67	5.53	3.54	2.46	1.81	1.38
	7.5	48.00	48.00	48.00	33.42	25.69	7.23	4.62	3.21	2.36	1.81
	8.75	48.00	48.00	48.00	33.42	25.69	7.23	4.62	3.21	2.36	1.81
	10	48.00	48.00	48.00	42.29	32.51	18.29	5.85	4.06	2.99	2.29
100,000	12.5	48.00	48.00	48.00	45.16	34.72	19.53	6.25	4.34	3.19	2.44
	15	48.00	48.00	48.00	47.12	36.23	20.38	6.52	4.53	3.33	2.55
	17.5	48.00	48.00	48.00	48.00	38.55	21.69	6.94	4.82	3.54	2.71
	20	48.00	48.00	48.00	48.00	40.14	22.58	7.23	5.02	3.69	2.82
	25	48.00	48.00	48.00	48.00	45.10	25.37	16.24	5.64	4.14	3.17
	30	48.00	48.00	48.00	48.00	46.82	26.34	16.86	5.85	4.30	3.29
	40	48.00	48.00	48.00	48.00	48.00	27.82	17.80	6.18	4.54	3.48
	50	48.00	48.00	48.00	48.00	48.00	29.86	19.11	6.64	4.88	3.73
	5.5	48.00	27.86	16.85	5.64	4.34	2.44	1.56	1.08	0.80	0.61
	6	48.00	32.70	19.78	6.62	5.09	2.86	1.83	1.27	0.93	0.72
	6.25	48.00	37.92	22.93	7.68	5.90	3.32	2.12	1.48	1.08	0.83
	7.5	48.00	48.00	29.96	20.05	7.71	4.34	2.77	1.93	1.42	1.08
Info found here is to be used as a guideline, Please contact sales@wdmrolls.com for questions. These capacities are based on the tonnage capacity of the machine. Because of the spring back of some of the materials, the minimum diameter may not be attainable. See the following chart for approximate minimum diameter. →	8.75	48.00	48.00	29.96	20.05	7.71	4.34	2.77	1.93	1.42	1.08
	10	48.00	48.00	37.91	25.38	19.51	5.49	3.51	2.44	1.79	1.37
	12.5	48.00	48.00	40.48	27.10	20.83	5.86	3.75	2.60	1.91	1.46
	15	48.00	48.00	42.24	28.27	21.74	6.11	3.91	2.72	2.00	1.53
	17.5	48.00	48.00	44.95	30.09	23.13	6.51	4.16	2.89	2.12	1.63
	20	48.00	48.00	46.81	31.33	24.08	6.77	4.34	3.01	2.21	1.69
	25	48.00	48.00	48.00	35.20	27.06	7.61	4.87	3.38	2.49	1.90
	30	48.00	48.00	48.00	36.54	28.09	7.90	5.06	3.51	2.58	1.98
	40	48.00	48.00	48.00	38.60	29.67	16.69	5.34	3.71	2.73	2.09
	50	48.00	48.00	48.00	41.43	31.85	17.92	5.73	3.98	2.93	2.24
	Wrought Iron/1010 MS, Soft Aluminium and Copper - ID									5.50	
	Mild Steel, i.e. M-1020, A-36 - ID									6.25	
	CR Sheet, Thin Galvanized, Half Hard Copper, SS -ID									7.50	
	AR Plate, T-1, Other Super Alloys - ID									10.00	