



PRESS SPECIFICATIONS

PRESS STROKE = 12"
SLIDE ADJUST = 12"
PRESS SPEED = 20 TO 50 S.P.M.
GEAR RATIO = 8.087 TO 1
MAIN MOTOR 75 H.P. DYNAMATIC
1690 TO 160 R.P.M.
CLUTCH 2002-2 MOD. "AK"

CROWN/DRIVE ASS'Y WT.= ---	64, 410#
UPRIGHTS EA.= 9000# = ----	18, 000#
TIE ROD ASS'Y X 4 = ------	9, 170#
SLIDE ASS'Y = ----------	25, 050#
BOLSTER = ----------	11, 737#
BED = ----------	35, 100#
TOTAL PRESS WT. APPROX. =	163, 467#



PUSHBUTTON ARRANGEMENT

1 RUN INCH
2 TOP STOP
3 OFF-INCH-SINGLE-CONT
4 STOP
5 SHUTHEIGHT INDICATOR
6 COUNTER
7 GROUND CONNECTED
8 LUBE FAULT
9 CONTROL-ON TOP-FAULT
10 MAIN & LUBE MOTOR RUNNING
11 HYD. OVRLOAD-NORMAL-INCH
12 CONTROL-TEST-NORMAL-RESET
13 MAIN & LUBE START
14 HYD-PRELOAD-OVRLOAD
15 CLUTCH-SLIDE
16 MAIN & LUBE STOP
17 OVRLOAD INCH
18 RAISE
19 FORWARD-REVERSE
20 LOWER
21 SPEED ADJUSTMENT
22 DIGITAL TACHOMETER
23 GEMCO QUICK SET PROG.LIMIT SWITCH

IMPORTANT NOTICE!

ALL GUARDS REMOVED TO FACILITATE SHIPPING MUST BE REPLACED PRIOR TO OPERATING MACHINE

WARNING!

OSHA REQUIRES PROTECTION OF OPERATOR BY GUARDING POINT OF OPERATION. A POINT OF OPERATION GUARD IS NOT INCLUDED WITH THIS PRESS. IT IS TO BE PROVIDED BY THE EMPLOYER.

UNIT #

CONFIDENTIAL
THIS DRAWING, INCLUDING ALL INFORMATION CONTAINED THEREON, IS THE EXCLUSIVE PROPRIETARY PROPERTY OF E. W. BLISS COMPANY, IT IS DISCLOSED WITH THE UNDERSTANDING IT WILL BE RETURNED IN CONFIDENCE AND WILL NEITHER BE DUPLICATED OR COPIED IN WHOLE OR IN PART NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH DISCLOSED

E.W. Bliss Company
HASTINGS, MICH. SALEM, OHIO

ORDER NO.	UNITS REQ'D.	TOTAL QUAN.
HP53792		

BREAK ALL SHARP EDGES

DR RCH 4MAR88
CH JES
APP'D

SC2-500 96x54 SG-TED
GENERAL PLAN
9650-D-1342

SCALE 1/10

TOLERANCE ALLOWANCE UNLESS OTHERWISE SPECIFIED
FRACTIONAL FINISH DIMENSIONS ± 1/64
DECIMAL FINISH DIMENSIONS ± .003

This Drawing and its Contents are the Proprietary Property of BLISS CLEARING NIAGARA, INC. and may only be used fo the purpose it is provided for

MAY 2 4 2004

NO.	DESCRIPTIONS	DATE	BY
	REVISIONS		

73