



REV.	DESCRIPTION
1	
2	

EZ-300-84-48 PRESS  
 CAPACITY 300 TONS  
 STROKE 10 IN.  
 ADJUSTMENT 6 IN.  
 STROKES PER MIN. 0-100  
 USABLE ENERGY @ 50 SPM = 75 IN. TONS  
 MAX. USABLE ENERGY FROM 54 TO 100 SPM = 85.7 IN. TONS

NOTE:  
 PRESS MAY BE SINGLE STROKED AS NOTED BELOW. A HIGHER RATE OF SGL. STROKING MAY CAUSE EXCESSIVE MAINTENANCE OF CLUTCH & BRAKE. THE SINGLE STROKING SPEED SHOULD NEVER EXCEED 75% OF THE CONTINUOUS SPEED OF THE PRESS.

CONTINUOUS SPM	SGL. STROKE SPM
50	22
75	13
100	7

INCLUDES EXHAUST MUFFLER ON CLUTCH SOLENOID VALVE.  
 AIR OPERATED AUTOMATIC FLYWHEEL BRAKE ELECTRICALLY INTERLOCKED WITH DRIVE MOTOR STOP CIRCUIT.  
 HELMS STRAIN LINKS MOUNTED ON CONNECTIONS.

LAST REVISION DATE 11-16-83 DRAWING BY L.P.	
T. PETERS THE MINSTER MACHINE CO. 1983	
DESIGNED BY	9-19-83 AGENS AGENS 3/9/82
DRAWING NO.	GENERAL ASSEMBLY
UNLESS OTHERWISE SPECIFIED	
TOLERANCE -	
FRACTIONS	±.010
DECIMALS	±.010
ANGLES	±.001
THREADS	±.001
WELDS	±.005
SIZE SHARP CORNER 0.03	